

MATERIAL SAFETY DATA SHEET

REVISION DATE: 10-08-2009

SUPERSEDES: 09-09-2008

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION

Specialty Construction Brands, Inc.
An H.B. Fuller Company
1105 S. Frontenac Street
Aurora, IL 60504
Phone: 1-800-323-7407

Medical Emergency Phone Number (24 Hours): 1-888-853-1758
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION

PRODUCT NUMBER: DSP 508 PART B
PRODUCT DESCRIPTION: Epoxy hardener
PRODUCT IDENTIFIER: 826928PM

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL STATE: Liquid
COLOR: Yellow
ODOR: Amine

Corrosive to eye tissue.
Causes skin burns. May cause allergic skin reaction.
Severe respiratory tract irritant.
Harmful if swallowed.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Corrosive to eye tissue. Can cause severe irritation, tearing, and burns that can quickly lead to permanent injury including blindness.

SKIN: Corrosive to skin tissue. Can cause chemical burns. May cause sensitization.

INHALATION: Can cause severe respiratory irritation, nausea, and headache.
Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination.

INGESTION: Ingestion is not an anticipated route of exposure. Harmful if swallowed. Corrosive to tissue. Can cause severe and permanent damage to mouth, throat, stomach. Aspiration may lead to lung damage.

LONG-TERM (CHRONIC) HEALTH EFFECTS

TARGET ORGAN(S): Central nervous system

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: No medical conditions affected by exposure.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT
Benzyl alcohol	100-51-6	50 - 70
Xylene-alpha-alpha'-diamine, m	1477-55-0	10 - 30

MATERIAL SAFETY DATA SHEET

Isophorone diamine	2855-13-2	10 - 30
Amine epoxy adduct		10 - 30
Butyl phenol, 4-tert	98-54-4	5 - 10

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. This corrosive material can cause immediate and permanent eye damage. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

IF ON SKIN: Wash with soap and water under a drench shower. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately.

IF VAPORS INHALED: Remove to fresh air. Restore breathing, if necessary. Keep warm and quiet. Call a physician.

IF SWALLOWED: Corrosive. Do not induce vomiting! Drink one glass of water followed by milk if available. Seek medical attention immediately. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT:	110C; 230F TCC
AUTOIGNITION TEMPERATURE:	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
UPPER EXPLOSIVE LIMIT (% in air):	Not established
EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Material will burn in a fire.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide Nitrogen containing gases

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:	Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, and the area in which the spill occurred. Never exceed any occupational exposure limits.
CLEAN-UP:	Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling:	Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area.
Storage:	Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

MATERIAL SAFETY DATA SHEET

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear chemical splash goggles when handling this product. Additionally, wear a face shield when the possibility of splashing of liquid exists. Do not wear contact lenses. Have an eye wash station available.

SKIN PROTECTION: Prevent contact with this product. Wear chemically resistant gloves, long sleeved shirt, an apron, and other protective equipment depending on conditions of use. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.

GLOVES: Butyl rubber

RESPIRATORY PROTECTION: Respiratory protection will be required when ventilation or other engineering controls can not reduce the exposure to acceptable levels. NIOSH approved air purifying respirator with organic vapor cartridge and dust/mist filter. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

VENTILATION: Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	OSHA PEL
Benzyl alcohol	Not established	Not established
Xylene-alpha-alpha'-diamine, m	Not established 0.1 mg/m3 Ceiling Skin absorption may potentially contribute to the overall exposure to this material.	Not established
Isophorone diamine	Not established	Not established
Amine epoxy adduct	Not established	Not established
Butyl phenol, 4-tert	Not established	Not established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid
COLOR: Yellow
ODOR: Amine
ODOR THRESHOLD: Not established
WEIGHT PER GALLON (lbs.): 8.67

MATERIAL SAFETY DATA SHEET

SPECIFIC GRAVITY:	1.04
pH:	11.5
FLASH POINT:	110C; 230F TCC
BOILING POINT (deg. C):	Not established
FREEZING/MELTING POINT (deg. C):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
EVAPORATION RATE:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
VOC, weight percent	Not determined

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Not established
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide Nitrogen containing gases

SECTION 11: TOXICOLOGICAL INFORMATION

COMPONENT	LD50/LC50
Benzyl alcohol	Oral LD50 Rat = 1230 mg/kg Dermal LD50 Rabbit = 2000 mg/kg
Xylene-alpha-alpha'-diamine, m	Oral LD50 Rat = 930 mg/kg Inhalation LC50 Rat = 350 ppm/4H Dermal LD50 Rabbit = 2000 mg/kg
Isophorone diamine	Not established
Amine epoxy adduct	Not established
Butyl phenol, 4-tert	Oral LD50 Rat = 3.25 ml/kg Dermal LD50 Rabbit = 2.52 ml/kg

TOXICOLOGY SUMMARY: No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is corrosive waste class D002. We recommend the required corrosivity testing on product to determine the appropriate waste category. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

DOT: UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (AROMATIC AND ALIPHATIC AMINES), 8, II
IATA: UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (AROMATIC AND ALIPHATIC AMINES), 8, II

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

MATERIAL SAFETY DATA SHEET

- U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.
- CANADIAN CEPA DSL: This product contains a component that is not on the DSL. If you are the importer of this product into Canada, contact H.B. Fuller for chemical tracking and notification information.
- EUROPEAN EINECS: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.
- JAPAN ENCS: This product is in compliance with the Japanese Existing and New Chemical Substances requirements.
- KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
---------------	------	---

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2B D1A

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
--------------------	-----	---------

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 3 FLAMMABILITY -- 1 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Specialty Construction Brands, Inc. from its suppliers, and because Specialty Construction Brands, Inc. has no control over the conditions of handling and use, Specialty Construction Brands, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Specialty Construction Brands, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of

MATERIAL SAFETY DATA SHEET

the user of Specialty Construction Brands, Inc. products to comply with all applicable federal, state and local laws and regulations.